









Handling Suction in urban areas Hydrostatic driving Noise reduction



Productivity Large capacity tank A Unloading folded/unfolded boom Efficient filtration system



Safety Obstacle detection & radar 3 stabilizers Safe access



Equipment Accessibility to suction nozzle m Carrier durability Simplified maintenance



The *EXVAC* benefits from all the RIVARD experience and offers excellent advantages in terms of productivity, ergonomics, reliability and safety.

The choice of the turbine, the location of the filters and their filtration system, the design of the tank, the articulation of the boom, the ease of maintenance, everything is thought to optimize the yields, to make the equipment reliable and to increase its operating life.

It is the ideal equipment for the realization of long distance suction works, in height or in depth of solid, liquid or pasty materials.

Technical features





Volvo & Mercedes carrier 26t 6x2/6x4 or 32t 8x4 PTAC 26t - 32t



Power recovered by the carrier's power take-off and transmitted to the turbine via a cut-off box



Dumping height 1700mm Integrated lid tank to control perfectly the emptying materials Tipping distance of 800mm 3 stabilizers for working/emptying Storage capacity of 7 or 10,5m³



Multi-stage industrial turbine with synchronous hydromechanical clutch (exclusivity to RIVARD) : different models 25000m³/h at 0,4 bar (26t) 30000m³/h at 0,4 or 0,5 bar (32t) Adjustment of the suction power by 3 speed ranges, 2 of which are variable



Suction boom Ø 250mm with 180° amplitude 6 hydraulic movements External antistatic hose Tipping arm folded or unfolded Proportional control of movements



6 or 8 filters, 102m² or 136m² of filtration surface (depending on the model) Independent, isolated and easily accessible filtration compartment

Integral filtration of the air flow with cleaning cycle



Compressor 186m³/h Operating pressure 7 bar




Ergonomic radio control for the piloting of the different functions Other frequencies available in case of interference + cable for wired work



Options and variants

- Hydrostatic drive with camera
- Remote start
- Remote steering control (buscan or flyover)
- Rotary bearing (4 different movements)
- Liquid and/ or dust level sensors
- Dry air and/ or oiled air reel 10m
- Equipotential reel 15m
- Various accessories available

Suction excavators range





- Z.I Le Grand Clos Daumeray 49640 Morannes s/Sarthe
- Contact@rivard.fr / +33 2 41 33 68 68
- www.rivard-international.com

RIVARD Services

- Training
 Spare parts
- Hotline
 · Technical centers



TUTAC